

# LED SUPERSTAR MR16 20 36° ADV 3.7 W/827 GU5.3

LED SUPERSTAR MR16 12 V advanced | Dimmable low-voltage LED reflector lamps MR16 with retrofit pin base



#### Areas of application

- As a downlight for marking walkways, doors, stairs, etc.
- Exhibitions, department stores
- Outdoor use in outdoor luminaires only (minimum IP65)
- Directional light sources
- Museums
- Hospitality
- Shops

### **Product benefits**

- Very low energy consumption
- Extremely long life
- No UV and near-IR radiation in the light beam
- Shockproof and vibration-proof
- Efficient generation of white light

#### **Product features**

- Professional LED lamp
- Dimmable (with many common dimmers, see also www.osram.com/dim)
- Base: GU5.3
- Lifetime: up to 25,000 h
- Mercury-free lamps





# Product datasheet

### Technical data

### **Electrical data**

Rated wattage	3.70 W
Nominal wattage	3.70 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	20 W
Rated luminous flux	210 lm
Operating frequency	5060 Hz
Power factor λ	0.70


### Photometrical data

Luminous intensity	600 cd
Nominal luminous flux	210 lm
Color temperature	2700 K
Color rendering index Ra	80
Light color as per EN 12464-1	Warm White
Standard deviation of color matching	≤5 sdcm
Nominal useful luminous flux 90°	220 lm
Rated useful luminous flux 90°	220 lm
Rated peak intensity	550 cd

# Light technical data

Beam angle	36 °
Warm-up time (60 %)	0.20 s
Starting time	0.1 s
Nominal beam angle	36.00 °
Rated beam angle (half peak value)	36.00 °

# Dimensions & weight



Overall length	51.0 mm
Diameter	50.0 mm
Outer bulb	MR51
Length	51.0 mm
Maximum diameter	50.0 mm

## Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen main.fact.at end of nom.life time	0.70

# Additional product data

Base (standard designation)	GU5.3		
Lamp mercury content	0.0 mg		
Mercury-free	Yes		
Appropriate disposal acc. to WEEE	Yes		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)		

### Product datasheet

## **Capabilities**

Dimmable	Yes <sup>1)</sup>

 $<sup>^{1)}</sup>$  With many common dimmers, see also www.osram.com/dim


#### Certificates & standards

Energy efficiency class	A+
Energy consumption	6 kWh/1000h

## **Country specific categorizations**

ILCOS	DRR-5-12-GU5,3-50/36	
Order reference	SSTMR1620AD 3,7	

## **Light Distribution**



### Spectral power distribution

### **Equipment / Accessories**

- Equipped with high-power LEDs
- Suitable for many commercially available electronic or conventional transformers

## Logistical Data

### Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321882264	LED SUPERSTAR MR16 20 36° ADV 3.7 W/827 GU5.3	Shipping carton box 6	311 mm x 89 mm x 112 mm	3.10 dm <sup>3</sup>	408.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For dimming conformity see

www.osram.com/DIM

For further products and actual information concerning LED lamps see

www.osram.com/ledlamps

For Guarantee see

www.osram.com/guarantee

Further information see

www.osram.com/low-voltage-ledlamps

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.