

# LEDinestra 6 W/827 ADV FR S14s

# LEDinestra advanced | Dimmable tubular LED lamps



### Areas of application

- Ideal for mirror lighting
- Hotels, restaurants
- Domestic applications
- Outdoor applications only in suitable luminaires

### **Product benefits**

- Long lifetime of up to 20,000 h
- Low energy consumption
- Good color rendering

#### Product features

- LED alternative to tubular incandescent lamps
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- For especially uniform illumination
- Mercury-free lamps
- Made in Germany





# Product datasheet

## Technical data

## **Electrical data**

Rated wattage	6.00 W
Nominal wattage	6.00 W
Nominal voltage	230 V
Operating frequency	50 Hz
Power factor $\lambda$	0.62
Claimed equiv. conventional lamp power	25 W

## Photometrical data

Nominal luminous flux	250 lm
Rated luminous flux	250 lm
Color temperature	2700 K
Color rendering index Ra	>80
Light color (designation)	Warm White

# Light technical data

Warm-up time (60 %)	0.00 s
Starting time	0.0 s

## Dimensions & weight



Overall length	300.0 mm
Diameter	29.0 mm
Outer bulb	T28,5
Length	300.0 mm

## Lifespan

Nominal lamp life time	20000 h

## Product datasheet

Rated lamp life time	20000 h
Number of switching cycles	50000
Lumen main.fact.at end of nom.life time	0.70
Lumen maintenance at end of service life	0.70

## Additional product data

Dage (standard decision)	\$14s		
Base (standard designation)	5145		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Frosted		
Appropriate disposal acc. to WEEE	Yes		
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In development, data preliminary/In preparation/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)		

# Capabilities

Dimmable	Yes <sup>1)</sup>
	. 65

 $<sup>^{1)}</sup>$  With many common dimmers, see also www.osram.com/dim


### **Certificates & standards**

Energy efficiency class	A	
Energy consumption	6 kWh/1000h	

## **Country specific categorizations**

ILCOS	DRL/F-6/827-230-S14S-29/300	
Order reference	LEDINESTRA 6W/8	

## Product datasheet



Others graphics

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899110311	LEDinestra 6 W/827 ADV FR S14s	Shipping carton box 5	348 mm x 260 mm x 80 mm	7.24 dm³	742.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.