

PRODUCT DATASHEET SPOT LED 68 8 W 4000 K IP44 DIM WT

LEDVANCE SPOT LED | LED spotlight luminaires



AREAS OF APPLICATION

- Replacement of halogen lamp spotlights
- General illumination
- Hotel rooms
- Bars, restaurants
- Accent lighting
- Galleries, museums
- Residential interiors

PRODUCT BENEFITS

- High luminous efficacy
- Design matches the LEDVANCE DOWNLIGHT luminaire family
- Energy savings of up to 90 % compared to halogen lamp spotlights
- Functional and minimalistic design
- Easy and quick installation
- External driver for extended flexibility (compatible with selected DALI drivers)
- 3 years guarantee

PRODUCT FEATURES

- Initial color consistency: \leq 4 SDCM
- Housing material: aluminum
- Lens material: PMMA
- Lifetime (L70/B50): up to 30,000 h (at 25 °C)



TECHNICAL DATA

Electrical data

Operating mode	Electronic control gear (ECG)	
Nominal wattage	8.00 W	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	
Power factor λ	>0.90	

Photometrical data

Color temperature	4000 K	
Luminous flux	670 lm	
Light color (designation)	Cool White	
Color rendering index Ra	>80	
Standard deviation of color matchi [PIM]	≤4 sdcm	

Light technical data

Beam angle	36 °
------------	------

Dimensions & weight

Diameter	81.0 mm	
Height	51.0 mm	
Mounting diameter	68 mm	

Colors & materials

Body material	Aluminum	
Product color	White	

Temperatures & operating conditions

Ambient temperature range	-2045 °C
---------------------------	----------

Lifespan

Lifespan L70 at 25 °C	50000 h
Lifespan L80 at 25 °C	40000 h
Lifespan L90 at 25 °C	20000 h
Number of switching cycles	100000

Capabilities

Dimmable	Yes	
Type of connection	Terminal, 2-pin	
LED module replaceable	Not replaceable	

Certificates & standards

Protection class II		
ype of protection IP44		
Protection class IK (shock resistance)	IK06	
Standards	CE/CB/TÜV SÜD/EAC/ROHS	

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075811270	SPOT LED 68 8 W 4000 K IP44 DIM WT	Shipping carton box 27	440 mm x 320 mm x 360 mm	50.69 dm³	10.08 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.