



# PRODUCT DATASHEET

## FLOODLIGHT LED 10 W 3000 K WT

LEDVANCE FLOODLIGHT LED | LED floodlight luminaires



### AREAS OF APPLICATION

- Replacement for floodlights with halogen lamps
- Car parks and underpasses
- Garages
- Public areas
- Building facades
- Construction areas

### PRODUCT BENEFITS

- Energy savings of up to 90 % compared to halogen lamp floodlights
- Optimized weight and size due to compact design
- Very homogenous light

### PRODUCT FEATURES

- Luminaire efficacy: up to 100 lm/W
- Beam angle: 100°
- Type of protection: IP65



## TECHNICAL DATA

### Electrical data

<b>Operating mode</b>	Electronic control gear (ECG)
<b>Nominal wattage</b>	10.00 W
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz
<b>Power factor <math>\lambda</math></b>	>0.90


### Photometrical data

<b>Color temperature</b>	3000 K
<b>Luminous flux</b>	800 lm
<b>Light color (designation)</b>	Warm White
<b>Color rendering index Ra</b>	$\geq 80$
<b>Standard deviation of color matching</b>	$\leq 5$ sdc <sub>m</sub>

### Light technical data

<b>Beam angle</b>	100.00 °
-------------------	----------

### Dimensions & weight



<b>Length</b>	117.0 mm
<b>Width</b>	127.0 mm
<b>Height</b>	39.0 mm

### Colors & materials

<b>Body material</b>	Polycarbonate (PC)
<b>Product color</b>	White

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...50 °C
----------------------------------	-------------

Lifespan

Lifespan L70 at 25 °C	50000 h
Lifespan L80 at 25 °C	30000 h
Lifespan L90 at 25 °C	15000 h
Number of switching cycles	30000

Capabilities

Dimmable	No
Type of connection	Cable, 3-pole
LED module replaceable	Not replaceable

Certificates & standards

Protection class	I
Type of protection	IP65
Standards	CE/CB/TÜV SÜD/EAC/ROHS
Protection class IK (shock resistance)	IK07

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075810938	FLOODLIGHT LED 10 W 3000 K WT	Shipping carton box 10	280 mm x 248 mm x 210 mm	14.58 dm <sup>3</sup>	5.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.