

---

## 64624 A1/51 100W 12V 20/CS 1/SKU



---

### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

---

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	54125
Product Name	64624 A1/51 100W 12V 20/CS 1/SKU
Application	Projector
LIF Code	A1/51
Product Remark	- p (Operating Position) = Horizontal

#### Electrical data

Nominal Wattage	100 W
Nominal Voltage	12 V
Type of Current	AC

#### Light technical data

Working Distance a (in)	1.024 in
Working Distance a (mm)	26 mm
Color Rendering Index	100
Average Rated Life	25 h


#### Physical attributes

Base	G5.3-4.8 BIPIN
Bulb Shape	MR11
Maximum Overall Length (in)	1.398 in
Maximum Overall Length (mm)	35.5 mm
Length l (in)	1.398 in
Length l (mm)	35.5 mm
Length l max. (in)	1.398 in
Length l max. (mm)	35.5 mm
Diameter d (in)	1.378 in
Diameter d (mm)	35.00 mm
Reflector Coating	35.00

#### Additional product data

Operating Position	p 90/15
Class	C (gas)

## Product datasheet



---

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54125	4050300013916	Folding box (SKU)	1	1.3 in x 1.3 in x 2 in	
54125	4050300664651	Shipping box (Case)	20	7.5 in x 3.2 in x 5.2 in	1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.