

---

## SIG 64015

Low-voltage halogen lamps, road traffic

---

### Areas of application

- Road traffic signalling systems



---

### Product benefits

- Low-voltage halogen lamps, therefore particularly high luminous flux
- Almost point-like light source for optimum focusing
- Virtually constant luminous flux throughout the life of the lamp
- Extremely long life compared to conventional lamps

# Product datasheet

## Technical data



### Electrical data

Nominal wattage	50.0 W
Nominal voltage	10.0 V
Test voltage	10 V

### Photometrical data

Nominal luminous flux	750 lm
-----------------------	--------

### Dimensions & weight



PK22s  
IEC 7004-47  
DIN 49742

IEC 7005-47  
DIN 49762

Diameter	11.5 mm
Overall length	42.0 mm
Light center length (LCL)	18.0 mm <sup>1)</sup>
Cable length	280.0 mm

<sup>1)</sup> Distance from the coil to the lug of base

### Lifespan

Nominal lamp life time	8000 h
------------------------	--------

### Additional product data

Base (standard designation)	PKX22s
-----------------------------	--------

### Capabilities

Burning position	p90 <sup>1)</sup>
------------------	-------------------

<sup>1)</sup> Only the permissible burning position may be used otherwise the lamp will fail prematurely / Lamps with transverse filaments should only be inclined perpendicular to the filament plane

### Country specific categorizations

Order reference	SIG 64015 CL 50
-----------------	-----------------

## Product datasheet

---

### Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300217543	OSRSIG64015	8334860	4733746	-

## Product datasheet

---

### Operating instructions

All halogen signal lamps operate at high temperature and pressure. They may therefore only be operated in signal equipment/luminaires specially designed for the purpose. Make sure that the lamps are protected against moisture during operation and in particular during relamping. When installing a new lamp, handle it by its protective cardboard sleeve.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300217543	SIG 64015	Folding carton box 1	70 mm x 23 mm x 25 mm	0.04 dm <sup>3</sup>	11.00 g
4050300217550	SIG 64015	Bundle 10	71 mm x 50 mm x 117 mm	0.42 dm <sup>3</sup>	117.00 g
4050300217567	SIG 64015	Shipping carton box 100	365 mm x 113 mm x 127 mm	5.24 dm <sup>3</sup>	1266.50 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---