
SIG 64002

SIRIUS | Low-voltage halogen lamps with dichroic reflector, road traffic



Areas of application

- Road and rail traffic signals

Product benefits

- Fixed adjustment of halogen tube to reflector provides high luminous intensity
- Nearly constant luminous intensity due to high quality reflector coating
- Very long life due to the halogen tube

Product features

- Connecting cables equipped with contacts/insulation widely resistant to corrosion and heat

Product datasheet

Technical data

Electrical data

Nominal wattage	20.0 W
Nominal voltage	12.0 V
Test voltage	12 V


Photometrical data

Nominal luminous flux	120 lm
-----------------------	--------

Light technical data

Aperture window, maximum	10.2 mm
--------------------------	---------

Dimensions & weight



Diameter	51.0 mm
Base diameter	24.5 mm
Overall length	46.5 mm
Cable length	105.0 mm

Lifespan

Nominal lamp life time	2000 h ¹⁾
------------------------	----------------------

¹⁾ Average lifespan at test voltage/current

Additional product data

Base (standard designation)	K23d
-----------------------------	------

Capabilities

Burning position	p90
------------------	-----

Product datasheet

Country specific categorizations

Order reference	SIG 64002 CL 20
------------------------	-----------------


Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300246505	OSRSIG64002HC	8334870	4739706	-

Product datasheet

Safety advice

All halogen signal lamps operate at high temperature and pressure. They may therefore only be operated in signal equipment/luminaires specially designed for the purpose. Make sure that the lamps are protected against moisture during operation and in particular during relamping.



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300246505	SIG 64002	Folding carton box 1	53 mm x 52 mm x 52 mm	0.14 dm ³	46.60 g
4050300246512	SIG 64002	Shipping carton box 10	301 mm x 63 mm x 232 mm	4.40 dm ³	516.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.