
64111

MINIWATT | Signal lamps for cars and motorcycles



Areas of application

- Interior lighting and reading lights

Product benefits

- OEM Quality
- Wide product range
- Reliable quality

Product features

- Hard-glass technology
- High luminous flux
- Luminous flux constant throughout the life of the lamp
- High color temperature (white light)
- Original spare parts

Technical data



Electrical data

Power input	5 W
Nominal wattage	5.00 W
Nominal voltage	12.0 V
Power input tolerance	±7.5 %
Test voltage	13.5 V

Photometrical data

Luminous flux	80 lm
Luminous flux tolerance	±15 %

Dimensions & weight



Length	33.0 mm
Diameter	41.0 mm

Lifespan

Lifespan B3	150 h
Lifespan Tc	500 h

Additional product data

Base (standard designation)	BA9s
-----------------------------	------

Certificates & standards

ECE category	-
--------------	---

Country specific categorizations

Order reference	64111 5W 12V BA
-----------------	-----------------

Product datasheet

Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4008321095015	OSRA64111	8328270	4739538	-
4050300647258	OSRA64111BLI2	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321095015	64111	Unpacked 1	23 mm x 9 mm x 11 mm	0.00 dm ³	4.25 g
4008321095022	64111	Folding carton box 10	63 mm x 51 mm x 119 mm	0.38 dm ³	36.20 g
4008321095039	64111	Shipping carton box 50	205 mm x 64 mm x 144 mm	1.89 dm ³	265.00 g
4050300647258	64111	Blister 2	59 mm x 14 mm x 53 mm	0.04 dm ³	11.00 g
4008321141576	64111	Shipping carton box 20	137 mm x 105 mm x 81 mm	1.17 dm ³	140.25 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.