



CorePro LEDIuster

CorePro lustre ND 4-25W E14 827 P45 FR

The frosted CorePro LEDluster is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E27 or E14 holder. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
Cap-Base	E14 [E14]
Bulb Shape	P45 [P 45mm]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	4-25W
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	250 lm
Luminous Flux (Rated) (Nom)	250 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	65 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
On another and Floridael	
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	4 W
Lamp Current (Nom)	35 mA
Wattage Equivalent	25 W


Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	instant full light
Power Factor (Nom)	0.4
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	85 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Approval and Application	
Suitable For Accent Lighting	No
Energy Efficiency Label (EEL)	A+
Energy Consumption kWh/1000 h	4 kWh
Product Data	
Full product code	871829178703700
Order product name	CorePro lustre ND 4-25W E14 827 P45 FR
EAN/UPC - Product	8718291787037

Datasheet, 2017, January 24 data subject to change

CorePro LEDluster

Order code	929001157502
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001157502

Dimensional drawing



LED ND 4-25W E14 827 220-240V P45 FR

Product	D	С
CorePro lustre ND 4-25W E14 827 P45 FR	45 mm	88 mm

