TUNGSRAM

Innovation is our heritage EST. 1896







Discharge - Single Ended Hot Restrike CSR800/SE/HR/UVC 93106222

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

Application areas



Film and Broadcast







Discharge - Single Ended Hot Restrike CSR800/SE/HR/UVC 93106222

Product data

93106222
70
Globe
Clear
30
145
8
190
213
U - Universal
Tungsram
G22

Performance data

Colour Code	956
Rated Lumens [lm]	64000
Weighted energy consumption [kWh/1000h]	880.0
Nominal chromaticity coordinate X	0.323
Nominal chromaticity coordinate Y	0.318
Nominal correlated colour temperature (CCT) [K]]	5600
Nominal lumens [lm]	64000
Colour Rendering Index (CRI) [Ra]	90



Discharge - Single Ended Hot Restrike CSR800/SE/HR/UVC 93106222

Electrical data

Rated power [W]	800.0
Lamp Current [A]	8.4
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	800
Nominal lamp voltage [V]	95

Logistic data

DUN Code	15994100020582	
EAN Code	5994100020585	
Pack Quantity	10	
Inner pack type	BOX	
Outer pack type	OUTER BOX	
Layer quantity	100 EUR, 130 UK	
Layer quantity EUR	100	
Layer quantity UK	130	
Pallet quantity EUR (PC)	600	
Pallet quantity UK (PC)	780	
Outer case size	370 x 154 x 230 (mm)	
Product status	Available	

Downloads & Links

Go to the catalog site (HTTP)

Information Lightcycle (PDF)

High-res images / Technical drawings (HTTP)

Disclaimer

Special Purpose Lamp, Not suited for household illumination

