
TUNGSRAM

Innovation is our heritage EST. 1896







Double Ended Quartzline TU P2/10 Q625T3/4CL 240/250V MIH 19698

Product information

Precision range of double ended Quartzline® lamps widely used in theatre and many other applications. A range from 350 W to 2,000 W with 3200K.

Application areas







Double Ended Quartzline TU P2/10 Q625T3/4CL 240/250V MIH 19698

Product data

Product Code	19698
Bulb Shape	Tubular
Bulb Diameter [mm]	10
Maximum Overall Length [mm]	190.6
Net weight per piece [g]	20
Gross weight per piece [g]	46
Brand	GE Lighting
Cap/Base	R7s

Performance data

16900	
625.0	
В	
300	
Nominal correlated colour temperature (CCT) [K]] 3200	
16900	
100	

Electrical data

Rated power [W]	625.0
Coil type	C-8
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	625.0
Nominal lamp voltage [V]	245



Double Ended Quartzline

TU P2/10 Q625T3/4CL 240/250V MIH 19698

Logistic data

DUN Code	00043168196987
EAN Code	0043168196987
Pack Quantity	12
Layer quantity	240 EUR, 300 UK
Layer quantity EUR	240
Layer quantity UK	300
Pallet quantity EUR (PC)	1440
Pallet quantity UK (PC)	1800
Outer case size	338 x 114 x 146 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

Lighting design tools & calculators (HTTP)

Entertainment Pocket brochure (PDF)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination

