

HF-Matchbox Blue

HF-M BLUE 124 LH TL/TL5/PL-L 230-240V

HF-Matchbox Blue is an affordable, reliable, compact, lightweight and high-frequency ballast for use with system wattages below 25 W in combination with TL mini, TL-D, TL5 and TL5c, PL-T/C, and PL-L/S lamps.The HF-M Blue range has a robust design, meets all relevant international safety and performance standards and has an energy efficiency index (CELMA EEI) of A2.

Product data

• General Information

Lamp typeTL/TL5/PL-LNumber of lamps1 piece/unitNumber of products60on MCB (16 A type8) (nom.)Automatic restartYes

• Operating and Electrical

Input voltage 230 to 240 V Input frequency 50-60 Hz Power factor 100% 0.64 load (nom.) 0.5 s Ignition time (max.) Mains voltage -8%-+6% performance (AC) -10%-+10% Mains voltage safety (AC) 1.8-2.1 W Power losses (nom.)

• Wiring

Connector type input terminals	Insert
Colour input termi-	Orange
Colour output termi-	Grey
nals Connector type	Insert
output terminals Cable length from	1.50 m
device to lamp Cable length hot-	0.30 m
wiring Wire strip length	8.0-9.0 mm
	0.0 7.0 1111

Input terminal cross section Output terminal cross section	0.50-1.50 mm ² 0.50-1.50 mm ²
Temperature T ambient (max.) T ambient (min.) T-Case maximum (max.)	40 °C -10 °C 75 °C
Mechanical and Housing Housing	LH
Emergency Operation Battery voltage lamp ignition	194-254 V
Approval and Applicatio	n
Approval marks	F-Marking CE marking VDE certificate CB Certificate
Product Data	
Full product code Order product name	871150053640230 HF-M BLUE 124 LH 230-240V

EAN/UPC – product Order code Local Code 871150053640230 HF-M BLUE 124 LH TL/TL5/PL-L 230-240V 8711500536402 53640230 HFMBLUE124LH



HF-Matchbox Blue

Numerator – quan-	1
tity per pack	
Numerator – packs	50
per outer box	

Material no. (12NC) Net weight (piece)

913700418066 0.045 kg



© 2015 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting