

MSI (Touring/Stage)

MSI 1200HR.1CT/10

The excellent color rendition characteristics of the light produced by the MSI (Touring/Stage) lamp helps ensure that audiences are always enthralled by the true natural colors and textures on the stage. What's more, the high luminous efficacy ensures that these lamps produce consistently high levels of lighting for a relatively small amount of energy consumption, making them the smart on-stage solution in more ways than one.

Product data

• General Information

Cap-Base SFC15.5-6 [SFC15.5-6]
Operating Position P [Parallel or Horizontal(HOR)]
Main Application Studio/Disco
Life To 50% Failures (Nom)

• Light Technical

Luminous Flux 90000 lm (Rated) (Nom)
Correlated Color 6000 K
Temperature (Nom)
Color Rendering 80
Index (Nom)

Operating and Electrical

Power (Rated) 1200 W (Nom) Voltage (Nom) 100 V

Controls and Dimming

Dimmable No

Warnings and Safety

 A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and

• Mechanical and Housing

Cap-Base Information SFC15.5-6

• Luminaire Design Requirements

Bulb Temperature 800 °C (Max)
Pinch Temperature 230 °C (Max)


• Product Data

Material Nr. (12NC) 924840600040 Net Weight (Piece) 0.110 kg

remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.




Dimensional drawing




MSI 1200HR

Product	D	0	Α	C (max)
MSI 1200HR.1CT/10	28 mm	10 mm	181 mm	220 mm

Photometric data







© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.