



# Actinic BL TL(-K)/TL-D(-K)

## Actinic BL TL TL-D 15W/10 1SL/25

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

### Product data

General Information		Operating and Electrical	
Cap-Base	G13 [ Medium Bi-Pin Fluorescent]	Power (Rated) (Nom)	15 W
Bulb Shape	T26 [ T 26mm]	Lamp Current (Nom)	0.34 A
Main Application	Reprography (R)	Voltage (Nom)	51 V
Life To 50% Failures (Nom)	8000 h	<b>Approval and Application</b>	
Useful Life (Nom)	5000 h	Mercury (Hg) Content (Nom)	5.0 mg
<b>Light Technical</b>		<b>UV</b>	
Color Code	10	UV-B/UV-A (IEC)	0.2 %
Color Designation	Actinic	UV-A Radiation 100Hr (IEC)	3.5 W
Chromaticity Coordinate X (Nom)	222	<b>Product Data</b>	
Chromaticity Coordinate Y (Nom)	210	Full product code	871150071093240
LLMF 2000 h Rated	25 %	Order product name	Actinic BL TL TL-D 15W/10 1SL/25
LLMF 6000 h Rated	30 %	EAN/UPC - Product	8711500710932


## Actinic BL TL(-K)/TL-D(-K)

Order code	928024801029
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928024801029

Net Weight (Piece)	59.600 g
--------------------	----------

### Dimensional drawing

Product	D	A	B	B	C
---------	---	---	---	---	---



TL-D 15W/10

