



TUV T8

TUV 75W HO 1SL/6

TUV T8 lamps are double-ended UVC (germicidal) lamps used in professional water and air disinfection units. TUV T8 lamps offer constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Moreover, they have a long and reliable lifetime, which allows maintenance to be planned for in advance.

Product data

General Information			
Cap base	G13 [Medium Bi-Pin Fluorescent		
Bulb shape	T26 [T 26mm]		
Main application	Disinfection		
Useful life (nom.)	9000 h		
System description	High Output (HO)		
Light Technical			
Colour designation	- [Not Specified]		
Lumen depreciation at end of useful lifetime	10 %		
Operating and Electrical			
Power (Rated) (Nom)	75 W		
Lamp current (nom.)	0.84 A		
Voltage (Nom)	110 V		
Approval and Application			
Mercury (Hg) content (nom.)	2.0 mg		

UV			
UV-C radiation	25.5 W		
Product Data			
Full product code	871150061851110		
Order product name	TUV 75W HO 1SL/6		
EAN/UPC - product	8711500618511		
Order code	61851110		
Local Code	75TUVHO		
Numerator – quantity per pack	1		
Numerator – packs per outer box	6		
Material no. (12NC)	928049404003		
Net weight (piece)	173.000 g		


Datasheet, 2017, January 30 data subject to change

TUV T8

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.

Dimensional drawing



Product	D	Α	В	В	С
TUV 75W HO 1SL/6	28 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm

TUV TL-D 75W HO

Photometric data

