

HPI-T

HPI-T 1000W/543 E40 220V 1SL/4

Quartz metal halide lamps with clear outer bulb

Product data

• General Information

Cap-Base	E40 [E40]
Operating Position	P [Parallel or Horizontal(HOR)]
Life To 5% Failures	3000 h
(Nom)	
Life To 10% Failures	5500 h
(Nom)	
Life To 20% Failures	8000 h
(Nom)	
Life To 50% Failures	12000 h
(Nom)	
System Description	na [-]

• Light Technical

Light Technical	
Color Code Luminous Flux (Min) Luminous Flux (Nom)	543 [CCT of 4300K] 79000 lm 85000 lm
Color Designation	Cool White (CW)
Lumen Maintenance 10000 h (Nom)	75 %
Lumen Maintenance 2000 h (Nom)	87 %
Lumen Maintenance 5000 h (Nom)	80 %
Chromaticity Coordinate X (Nom)	370
Chromaticity Coordinate Y (Nom)	380
Correlated Color Temperature (Nom)	4300 K
Luminous Efficacy (rated) (Nom)	86 lm/W
Color Rendering Index (Nom)	57

• Operating and Electrical

Power (Rated)	1000 ₩
(Nom)	
Lamp Current Run-	14.2 A
Up (Max)	
Lamp Current (EM)	8.25 A
(Nom)	
Ignition Supply	198 V
Voltage (Max)	
Ignition Supply	198 V
Voltage (Min)	
Ignition Time (Max)	30 s
Voltage (Max)	140 V
Voltage (Min)	120 V
Voltage (Nom)	220 V
- ' '	

• Controls and Dimming

Dimmable No

• Mechanical and Housing

Bulb Finish Clear

• Approval and Application

Energy Efficiency A+ Label (EEL) Mercury (Hg) 86 mg Content (Nom)

• Luminaire Design Requirements

Bulb Temperature 555 °C (Max)



HPI-T

Cap-Base Temperature (Max)

300 °C

• Product Data

Full product code Order product name EAN/UPC - Product 871150018373645

HPI-T 1000W/543 E40 220V 1SL/4

8711500183736

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures


928482600096 Order code

Numerator - Quantity Per Pack Numerator - Packs 4 per outer box

Material Nr. (12NC) 928482600096 0.370 kg Net Weight (Piece)

- For use with control gear designed for high-pressure mercury lamps
- · A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




HPI-T, 1000W, E40

HPI-T 1000W/543 E40

Product	D	0	L	С
HPI-T 1000W/543 E40 220V 1SL/4	66 mm	80 mm	240 mm	382 mm



Photometric data





© 2016 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.