



Halogen reflector

13631 250W GX5.3 24V 1CT/24

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information			
Cap-Base	GX5.3 [GX5.3]		
Philips Code	13631		
ANSI Code	ELC-FA		
LIF Code	A1/259		
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]		
Main Application	Projection		
Life to 50% Failures (Nom)	50 h		
Light Technical			
Luminous Flux (Rated) (Nom)	1500 lm		
Correlated Color Temperature (Nom)	3400 K		
Color Rendering Index (Nom)	100		
Operating and Electrical			
Power (Rated) (Nom)	250 W		

Voltage (Nom)	24 V		
Controls and Dimming			
Dimmable	Yes		
Mechanical and Housing			
Bulb Material	Quartz-UV Open		
Reflector Finish	Facetted		
Filament Dimensions WxH	-		
Luminaire Design Requirements			
Bulb Temperature (Max)	900 °C		
Pinch Temperature (Max)	400 °C		
Working Distance WD	32 mm		
Product Data			
Full product code	871150041075730		


Datasheet, 2018, July 24 data subject to change

Halogen reflector

Order product name	13631 250W GX5.3 24V 1CT/24		
EAN/UPC - Product	8711500410757		
Order code	924010520594		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	24		

Material Nr. (12NC)	924010520594
Net Weight (Piece)	0.026 kg

Dimensional drawing



Product	D (max)	C (max)
13631 250W GX5.3 24V 1CT/24	50.67 mm	44.45 mm

