



# Halogen non-reflector

## 14530 300W GY6.35 24V 1CT/24

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

### Product data

General Information	
Cap-Base	GY6.35 [ GY6.35]
Philips Code	14530
ANSI Code	FLW
LIF Code	-
Operating Position	S90 [ Standing +/-90D or Base Down (BDH)]
Main Application	Projection
Life to 50% Failures (Nom)	50 h

Light Technical	
Luminous Flux (Rated) (Nom)	10450 lm
Correlated Color Temperature (Nom)	3500 K
Color Rendering Index (Nom)	100

Operating and Electrical	
Power (Rated) (Nom)	300 W
Voltage (Nom)	24 V

Mechanical and Housing	
Bulb Material	Quartz-UV Open
Filament Shape	Flat
Filament Dimensions WxH	6.7x4.6


Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	400 °C

Product Data	
Full product code	871150042461730
Order product name	14530 300W GY6.35 24V 1CT/24
EAN/UPC - Product	8711500424617
Order code	924041420594
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	924041420594
Net Weight (Piece)	0.006 kg

## Halogen non-reflector

### Dimensional drawing



14530 300W GY6.35 24V

Product	D (max)	L (min)	L (max)	L	P (max)	P	P (min)	C (max)
14530 300W	13.5 mm	32.75	33.25	33	1.30 mm	1.25	1.20	55 mm
GY6.35 24V		mm	mm	mm		mm	mm	
1CT/24								

