



# MASTER TL5 High Output Secura

# MASTER TL5 HO Secura 54W/840 UNP/40

This TL5 High Output Secura lamp (tube diameter 16 mm) has a protective coating that keeps glass and lamp components together in the event of accidental breakage. The lamp is easily identifiable by a blue ring at one end. Application areas are all places where glass shatters can disturb operations and can have an impact on product and people safety, e.g. the food and beverage industry. This lamp is compliant with HACCP regulations and supports HACCP certification.

#### **Product data**

**General Information** 

Cap-Base	G5 [ G5]
Life to 50% Failures Preheat (Nom)	30000 h
System Description	High Output
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	97 %
LSF Preheat 20000 h Rated	84 %
Light Technical	
Color Code	840 [ CCT of 4000K]
Luminous Flux (Nom)	4450 lm
Luminous Flux (Rated) (Nom)	4500 lm
Color Designation	Cool White (CW)
Luminous Efficacy (@ Max Lumen, Rated) (Non	n) 93 lm/W
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	83 lm/W

Color Rendering Index (Max)	85
Color Rendering Index (Min)	80
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91%
LLMF 20000 h Rated	90 %
Operating and Electrical	
Power (Nom)	54.1 W
Lamp Current (Nom)	0.455 A
Temperature	
Design Temperature (Nom)	35 ℃

Datasheet, 2019, December 13 data subject to change


# **MASTER TL5 High Output Secura**

Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Cap-Base Information	Green Plate	
Approval and Application		
Energy Efficiency Label (EEL)	A+	
Mercury (Hg) Content (Nom)	1.4 mg	
Energy Consumption kWh/1000 h	59 kWh	
Product Data		
Full product code	871150095231855	

Order product name	MASTER TL5 HO Secura 54W/840
	UNP/40
EAN/UPC - Product	8711500952318
Order code	927929184018
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	927929184018
Net Weight (Piece)	143.280 g
ILCOS Code	FDH-54/40/1B-L/P-G5-16/1150

## **Warnings and Safety**

# Dimensional drawing





#### Product

MASTER TL5 HO Secura 54W/840 UNP/40

## TL5 HO Secura 54W/840

## Photometric data







LDPO\_TL5HO8SE\_840-Spectral power distribution Colour

# **MASTER TL5 High Output Secura**


## Lifetime





## LDLE\_TL5HO8SE\_0001-Life expectancy diagram







© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.