



TL-D Colored

TL-D Colored 58W Yellow 1SL/25

This TL-D lamp (tube diameter 26 mm) helps to create special effects and atmospheres or attract attention by using red, green, blue and yellow light. Apart from using the specific colors, it is also possible to mix the colors to create white light. This lamp offers a high light output, thanks to the use of basic powders. Application areas include shops and showrooms, bars and restaurants, demonstration areas, sign lighting and entertainment stores.

Product data

General Information				
Cap-Base	G13 [Medium Bi-Pin Fluorescent]			
Life To 10% Failures (Nom)	12000 h			
Life to 50% Failures (Nom)	15000 h			
Light Technical				
Color Code	160			
Luminous Flux (Nom)	2250 lm			
Luminous Flux (Rated) (Nom)	2250 lm			
Color Designation	Yellow			
LLMF 2000 h Rated	80 %			
Operating and Electrical				
Power (Rated) (Nom)	58.5 W			
Lamp Current (Nom)	0.670 A			
Voltage (Nom)	111 V			
Temperature				
Design Temperature (Nom)	25 ℃			

Controls and Dimming				
Dimmable	Yes			
Approval and Application				
Energy Efficiency Label (EEL)	В			
Mercury (Hg) Content (Nom)	13.0 mg			
Energy Consumption kWh/1000 h	70 kWh			
Product Data				
Full product code	871150095447340			
Order product name	TL-D Colored 58W Yellow 1SL/25			
EAN/UPC - Product	8711500954473			
Order code	928049001605			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	25			
Material Nr. (12NC)	928049001605			
Net Weight (Piece)	167.000 g			


Datasheet, 2018, September 24 data subject to change

TL-D Colored

Warnings and Safety


• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D Colored 58W	28.0 mm	1500.0 mm	1507.1 mm	1504.7 mm	1514.2 mm
Yellow 1SL/25					

Photometric data







© 2018 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.