



# MASTERC colour CDM-R111 Elite

Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	46 lm/W
Color Rendering Index (Min)	87
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	1750 lm

## Operating and Electrical

Power (Nom)	39.1 W
Lamp Current (EM) (Nom)	0.440 A
Re-Ignition Time (Min) (Max)	15 min
Warm Up Time to 60% Light (Nom)	120 s
Ignition Time (Max)	30 s
Voltage (Max)	97 V
Voltage (Min)	81 V
Voltage (Nom)	89 V

## Controls and Dimming

Dimmable	No
Run-Up Time 90% (Max)	3 min

## Mechanical and Housing

Bulb Finish	Reflector
-------------	-----------


## Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	4.7 mg
Energy Consumption kWh/1000 h	43 kWh

## Product Data

Full product code	871829168944700
Order product name	MASTERC colour CDM-R111 Elite CDM-R111 Elite 35W/930 GX8.5 24D
EAN/UPC - Product	8718291689447
Order code	928195405330
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	928195405330
Net Weight (Piece)	96.000 g
ILCOS Code	MRS/UB-35/930-H-GX8.5-111/88/24


## Dimensional drawing



CDM-R111 Elite 35W/930 24D

Product	D (max)	C (max)
MASTERC colour CDM-R111 Elite CDM-R111 Elite 35W/930 GX8.5 24D	111 mm	95 mm

## Photometric data



1190° / 180° / 190°

LDPO\_CDMR111E\_0001-Spectral power distribution Colour

## MASTERCcolour CDM-R111 Elite

