
TUNGSRAM

Innovation is our heritage EST. 1896







Single Ended Halogen CP93 230-240V 88508

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs - Chromised seal protection up to 500° C.

Application areas









Single Ended Halogen CP93 230-240V 88508

Product data

Light Center Length [mm]	63.5
Product Code	88508
Bulb Shape	Tubular
Bulb Diameter [mm]	35
Maximum Overall Length [mm]	130
Net weight per piece [g]	60
Gross weight per piece [g]	150
Brand	GE Lighting
Cap/Base	G22

Performance data

Rated Lumens [lm]	33000
Weighted energy consumption [kWh/1000h]	1200.0
Energy efficiency class (EEC)	В
Rated Life [h]	200
Nominal correlated colour temperature (CCT) [K]] 3200	
Nominal lumens [lm]	33000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	1200.0
Coil type	C-13D
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	1200.0
Nominal lamp voltage [V]	240



Single Ended Halogen CP93 230-240V 88508

Logistic data

DUN Code	10043168885086
EAN Code	0043168885089
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR, 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	190 x 350 x 126 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

Lighting design tools & calculators (HTTP)

Entertainment Pocket brochure (PDF)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination

