



1272

kWh/1000h

30

lumens/watt

Single Ended Halogen

CP110 OC-1200 80V

93106475

Product information

Quartz lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W
-Range of bases to meet the needs of OEMs -
Chromised seal protection up to 500° C.

Application areas



Film and Broadcast



Theatre



Product data

Product Code	93106475
Light Center Length [mm]	63.5
Bulb Shape	Tubular
Bulb Diameter [mm]	26
Maximum Overall Length [mm]	140
Net weight per piece [g]	95
Gross weight per piece [g]	165
Brand	TungsrAm
Cap/Base	G22

Performance data

Rated Lumens [lm]	36000
Weighted energy consumption [kWh/1000h]	1272.0
Energy efficiency class (EEC)	G
Rated Life [h]	300
Nominal correlated colour temperature (CCT) [K]	3300
Nominal lumens [lm]	36000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	1200.0
Coil type	C-13D
Dimming Capability	Yes
Ballast Required	Yes
Nominal power [W]	1200
Nominal lamp voltage [V]	80

Logistic data

DUN Code	15994100021039
EAN Code	5994100021032
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR, 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	350 x 190 x 120 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination